

SAFETY DATA SHEET of: SPA METAL CLEAN

Revision date: Thursday, June 9, 2022

S109.008

SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

SPA METAL CLEAN

UFI: 8U0S-T95J-110K-PKS3

1.2 Relevant identified uses of the substance or mixture and uses advised against:

additief voor privé spa's

Concentration in use: raadpleeg technische fiche

1.3 Details of the supplier of the safety data sheet:

SPA-PLUS BV

Industrieweg 8B

5571 LJ Bergeijk

Phone: 0497555562 — E-mail: pieter@spa-plus.eu — Website: http://www.spa-plus.eu/

1.4 Emergency telephone number:

+32 70 245 245

SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008

H314 Skin Corr. 1A H318 Eye Dam. 1

2.2 Label elements:

Pictograms



Signal word

Danger

Hazard statements

H314 Skin Corr. 1A H318 Eye Dam. 1: Causes severe skin burns and eye damage.

Precautionary statements

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

P501: Dispose of contents/container in accordance with

local/regional/national/international regulations.

Contains

None

2.3 Other hazards:

None

SECTION 3: Composition/information on ingredients:

Citric Acid	≤ 3 %	CAS number:	77-92-9
		EINECS:	201-069-1
		REACH Registration number:	01-2119457026-42
		CLP Classification:	H319 Eye Irrit. 2 H335 STOT SE 3
2-bromo-2-nitropropane-1,3-diol	≤ 0.3 %	CAS number:	52-51-7
		EINECS:	200-143-0
		REACH Registration number:	/
		CLP Classification:	H301 Acute tox. 3 H312 Acute tox. 4 H315 Skin Irrit. 2 H318 Eye Dam. 1 H331 Acute tox. 3 H335 STOT SE 3 H400M10 H411 Aquatic Chronic 2
		Additional data:	M (Acute) = 10

For the full text of the H phrases mentioned in this section, see section 16.

SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact: Remove contaminated clothing, rinse skin with plenty of water and immediately

transport to hospital.

Eye contact: Thoroughly rinse with water (contact lenses to be removed if this is easily done)

then take to physician.

Ingestion: Rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: Let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: Caustic, redness, pain, serious burns

Eye contact: Caustic, redness, blurred vision, pain

Ingestion: Caustic, lack of breath, vomiting, blisters on lips and tongue, burning pain in

mouth and throat, gullet and stomach

Inhalation: Headache, dizziness, nausea, drowsiness, unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed:

None

SECTION 5: Fire-fighting measures:

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

None

5.3 Advice for firefighters:

Extinguishing agents to be avoided: None

SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

6.4 Reference to other sections:

For further information, check sections 8 & 13.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

additief voor privé spa's

SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

 $Listing \ of \ the \ hazardous \ ingredients \ in \ section \ 3, of \ which \ the \ workplace \ exposure \ limit \ values \ are \ known$

/

8.2 Exposure controls:

Inhalation protection:	Use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
Skin protection:	Handling with Viton-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,7 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	
Environmental controls:	Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions. For further information, check sections 6 and 13.	
Engineering controls:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Adequate ventilation should be provided so that exposure limits are not exceeded. For further information, check section 7.	

SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Appearance/20°C: Liquid
Colour: colourless
Odour: characteristic

Melting point/melting range: 0 °C

Boiling point/Boiling range: $100 \, ^{\circ}\text{C} - 100 \, ^{\circ}\text{C}$ Flammability (solid, gas): Not applicable

Lower flammability or explosive limit, (Vol

%):

Upper flammability or explosive limit, (Vol

%):

Flash point: /

Auto-ignition temperature: /
Decomposition temperature: /
pH: 0.9
pH 1% diluted in water: /

Kinematic viscosity, 40°C: 1 mm²/s

Solubility in water:

Partition coefficient: n-octanol/water:

Vapour pressure/20°C;:

Relative density, 20°C:

Vapour density:

Completely soluble

Not applicable

1.0250 kg/l

Not applicable

Particle characteristics: /

9.2 Other information:

Dynamic viscosity, 20°C: 1 mPa.s

Sustained combustion test: /

Evaporation rate (n-BuAc = 1): 0.300

Volatile organic component (VOC): /

Volatile organic component (VOC): 0.000 g/l

SECTION 10: Stability and reactivity:

10.1 Reactivity:

Stable under normal conditions.

10.2 Chemical stability:

Extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

None

10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

None

10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected.

SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

a) acute toxicity:

Not classified according to the CLP calculation method

Calculated acute toxicity, ATE oral: > 2,000 mg/kg
Calculated acute toxicity, ATE dermal: > 2,000 mg/kg

Citric Acid	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5,000 mg/kg ≥ 5,000 mg/kg ≥ 50 mg/l
2-bromo-2-nitropropane-1,3-diol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	100 mg/kg 1,100 mg/kg 3 mg/l

b) skin corrosion/irritation:

H314 Skin Corr. 1A H318 Eye Dam. 1: Causes severe skin burns and eye damage.

c) serious eye damage/irritation:

H314 Skin Corr. 1A H318 Eye Dam. 1: Causes severe skin burns and eye damage.

d) respiratory or skin sensitisation:

Not classified according to the CLP calculation method

e) germ cell mutagenicity:

Not classified according to the CLP calculation method

f) carcinogenicity:

Not classified according to the CLP calculation method

g) reproductive toxicity:

Not classified according to the CLP calculation method

h) STOT-single exposure:

Not classified according to the CLP calculation method

i) STOT-repeated exposure:

Not classified according to the CLP calculation method

i) aspiration hazard:

Not classified according to the CLP calculation method

11.2 Information on other hazards:

No additional data available

SECTION 12: Ecological information:

12.1 Toxicity:

Citric Acid	LC50 (Fish):	440 - 760 mg/l (48h)
	LC50 (Daphnia):	1535 mg/l (24h)
	EC50 (Daphnia):	1535 mg/l (24h)

12.2 Persistence and degradability:

No additional data available

12.3 Bioaccumulative potential:

No additional data available

12.4 Mobility in soil:

Water hazard class, WGK (AwSV):

Solubility in water: Completely soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Endocrine disrupting properties:

No additional data available

12.7 Other adverse effects:

No additional data available

SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

The product may be discharged in the indicated percentages of utillization, provided it is neutralised to pH 7. Possible restrictive regulations by local authority should always be adhered to.

SECTION 14: Transport information:



14.1 UN number:

3265

14.2 UN proper shipping name:

UN 3265 Corrosive liquid, acidic, organic, n.o.s. (mixture with Citric Acid), 8, III, (E)

14.3 Transport hazard class(es):

Class(es): 8
Identification number of the hazard: 80

14.4 Packing group:

Ш

14.5 Environmental hazards:

Not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics: Risk of burns. Risk to the aquatic environment and the sewerage system.

Additional guidance: Not applicable

14.7 Maritime transport in bulk according to IMO instruments:

Not applicable

SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV): 1
Volatile organic component (VOC): /

Volatile organic component (VOC): 0.000 g/l

Composition by regulation (EC) 648/2004: Preservatives (2-Bromo-2-Nitropropane-1,3-Diol)

15.2 Chemical Safety Assessment:

No data available

SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of Dangerous

Goods by Road

ATE: Acute Toxicity Estimate

BCF: Bioconcentration factor

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of chemicals

EINECS: European INventory of Existing commercial Chemical Substances

LC50: median Lethal Concentration for 50% of subjects

LD50: median Lethal Dose for 50% of subjects

Nr.: Number

PTB: Persistent, Toxic, Bioaccumulative
STOT: Specific Target Organ Toxicity
UFI: Unique Formula Identifier

vPvB: very Persistent and very Bioaccumulative substances

WGK: Water hazard class

WGK 1: Slightly hazardous for water

WGK 2: Hazardous for water

WGK 3: Extremely hazardous for water

Legend to the H Phrases used in the safety data sheet

H301 Acute tox. 3: Toxic if swallowed. H312 Acute tox. 4: Harmful in contact with skin. H314 Skin Corr. 1A H318 Eye Dam. 1: Causes severe skin burns and eye damage. H315 Skin Irrit. 2: Causes skin irritation. H318 Eye Dam. 1: Causes serious eye damage. H319 Eye Irrit. 2: Causes serious eye irritation. H331 Acute tox. 3: Toxic if inhaled. H335 STOT SE 3: May cause respiratory irritation. H400M10: Very toxic to aquatic life. H411 Aquatic Chronic 2:

Toxic to aquatic life with long lasting effects.

CLP Calculation method

On basis of test data for corrosivity, CLP Calculation method for all other classes

Reason of revision, changes of following items

Section: 3

SDS reference number

ECM-4564,10

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2020/878. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.