



## RECOATER for CONCRETE PAVERS (WL5)

WET LOOK - GLOSS FINISH - SOLVENT BASED

{60102110/3.78 L}  
{60102108/18.93 L}

### UPDATE

#### May 3, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: [techniseal.com](http://techniseal.com)  
Canada and U.S.A.: dial 1 800 465-7325  
Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

- Recommended for driveways, parking lots, walkways and patios .

### PROPERTIES

- Enhances the colour of pavers
- Ideal for driveways, patios and walkways
- Stain guard - forms a protective film
- Solvent based

### DESCRIPTION

Made of acrylic and plasticizers, WL5 Recoater is specially designed to protect concrete pavers. Formulated for previously sealed surfaces, it prevents deterioration due to chemical products such as de-icing salts, while providing resistance to acids and alkalis. Its transparent film stops the penetration of contaminants, facilitating the maintenance of pavers

### DIRECTIONS

#### BEFORE YOU BEGIN

- Do not apply to stamped or poured concrete. • Application to natural stone or wet-cast pavers: Contact Techniseal® at 1 800 465 7325. • Apply only to material previously sealed with this product or with Techniseal® Wet Look WL4 Protector. • Wait until the Protector is worn before recoating the surface (minimum 2 years). • Wear adequate protective clothing and an approved respirator. • **ALWAYS TEST** on a small hidden area of approximately 0.4 m<sup>2</sup> (4 sq. ft.) to ensure that result meets your expectations (see Warranty).

#### SURFACE PREPARATION (ESSENTIAL)

1. Cover vegetation, vehicles and adjacent surfaces that are not to be treated.
2. Remove stains with the appropriate Techniseal® stain removers.
3. Prepare the entire surface with HD Paver Prep from Techniseal® (efflorescence cleaner), as directed on product label. Do not use Paver Prep on natural stone or wet-cast pavers.

## APPLICATION

### Application Conditions:

- Surface must be clean, dry and warm to the touch.
- Temperature must be between 10°C and 30°C.
- No rain forecasted for the next 24 hours.
- Sprinkler system must be turned off.
- Use a consistent application method over entire surface.

### Necessary Tools:

- Low-pressure airless sprayer (< 50 psi) or acetone-resistant pump sprayer (optional)
- Slit-Foam Roller from Techniseal® and solvent-resistant paint tray

Do not dilute. Shake well or stir product before and during application.

**Sprayer Application (Best Practice):** Work in sections of no more than 4.6 m<sup>2</sup> (50 sq. ft.). **Saturate** a section with a single coat of Protector. With the roller, remove excess on the surface before it dries. Repeat for subsequent sections, maintaining a wet edge in order to prevent overlap marks.

**Roller Application:** **Saturate** the surface with a single coat of Protector, avoiding accumulation of excess product. Maintain a wet edge in order to prevent overlap marks.

**Traffic:** Pedestrian: 24 h. / Vehicular: 48 to 72 h. Block access during that period.

## CAUTION

- Do not attempt sprayer application on windy days.
- Do not apply this product over a blotchy or hazed surface.
- This product will make the surface more slippery when wet. If slipping is a problem, consider Surefoot Additive from Techniseal® (245-970).
- An over-accumulation of product could lead to surface whitening.
- Extreme climate or heavy traffic could limit product longevity.

## COVERAGE

Single-coat application: 3.78 L cover up to 14 m<sup>2</sup> (150 sq. ft.) / 18.93 L cover up to 70 m<sup>2</sup> (750 sq. ft.)

Coverage will depend on surface porosity and joint width.

## STORAGE

Store in a cool, dry place.

## CLEANING & DISPOSAL

Wash tools with lacquer thinner. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

## PACKAGING

Product code	Size	Units per box	Units per pallet
60102110 (241-103)	3.78 L	4	180
60102108 (241-106)	18.93 L	—	48

## WARNING

---

**CONTENTS MAY CATCH FIRE. CONTENTS HARMFUL. MAY IRRITATE EYES. MAY IRRITATE SKIN.** Do not smoke. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection. **FIRST AID TREATMENT** **Contains:** Acetone; Solvent naphtha (petroleum), light arom; 1,2,4-trimethylbenzene. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

**Coating Category:** Waterproofing Concrete/ Masonry Sealers (VOC Concentration Limit: 400g/L)

**EMERGENCY PHONE CANUTEC (613) 996-6666. SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.**

## SHIPPING

---

### Land and sea

UN1993

Flammable liquid, N.O.S. (acetone)

Class: 3

PG: II

### Exemption:

- 18.93 liters needs to be transported under the hazmat regulation for any carrier that is operating a company that the mean is to transport and move mail and merchandises Trucks will need placards & the driver will need a hazmat permit. • It is possible to carry up to 8 x 18.93 liters without being regulated under the \*Gross Mass exemption.
- 3.78 liters are exempted for transport up to a total quantity of 500 kg (approx 130 x 1 gallon), according to the 500kg special exemption • It is possible to carry up to 40 x 3.78 liters without being regulated under the \*Gross Mass exemption.
- 500 kg Gross Mass Exemption: It is possible for the buyer or the user to transport up to 500kg in a vehicle.

## LIMITED WARRANTY

---

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 0.4 m<sup>2</sup> – 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 0.4 m<sup>2</sup> (4 sq. ft.). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose

