



PROTECTOR for CONCRETE PAVERS (WL4)

WET LOOK - GLOSS FINISH - SOLVENT BASED

(60301534 / 1 gal.)

(60301535 / 5 gal.)

UPDATE

April 23, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

NOTE: This product is not sold in the states of Utah and California (San Francisco Bay Area, counties of LA, Orange, Riverside and San Bernardino)

APPLICATIONS

Ideal for driveways, patios and walkways

PROPERTIES

Enhances the color of pavers

Ideal for driveways, patios and walkways

Stain guard - forms a protective film

For bare surfaces only

Solvent based

DESCRIPTION

Made of acrylic and plasticizers, WL4 Protector is specially designed to protect concrete pavers. Formulated for bare surfaces, it prevents deterioration due to chemical products such as de-icing salts, while providing resistance to acids and alkalis. Its transparent film stops the penetration of contaminants, facilitating the maintenance of pavers.

DIRECTIONS

BEFORE YOU BEGIN

- Do not apply to natural stone or to wet-cast pavers, stamped or poured concrete. • Apply only to bare material*. Wait until the Protector is worn to recoat the surface (minimum 2 years) with WL5 Recoater from Techniseal[®].
- With the appropriate Techniseal[®] stripper, remove any unknown coating that was previously applied. • Wear adequate protective clothing and an approved respirator. • **ALWAYS TEST** on a small hidden area of approximately 4 sq. ft. to ensure that result meets your expectations (see Warranty).

*ABSORPTION TEST: Sprinkle a few drops of water on surface. If water is absorbed, move on to the next point. If water is repelled, do not apply this product.

SURFACE PREPARATION (ESSENTIAL):

1. Cover vegetation, vehicles and adjacent surfaces that are not to be treated.
2. Remove stains with the appropriate Techniseal® stain removers.
3. Prepare the entire surface with Techniseal® Paver Prep (efflorescence cleaner), as directed on product label.

APPLICATION**Application Conditions:**

- Surface must be clean, dry and warm to the touch.
- Temperature must be between 50°F and 86°F.
- No rain forecasted for the next 24 hours.
- Sprinkler system must be turned off.
- Use a consistent application method over entire surface.

Necessary Tools:

- Low-pressure airless sprayer (< 50 psi) or solvent-resistant pump sprayer (optional)
- Techniseal® Slit-Foam Roller and solvent-resistant paint tray

Do not dilute. Shake well or stir product before and during application.

Sprayer Application (Best Practice): Work in sections of no more than 50 sq. ft. **Saturate** a section with a single coat of protector. With the roller, remove excess on the surface before it dries. Repeat for subsequent sections, maintaining a wet edge in order to prevent overlap marks.

Roller Application: **Saturate** the surface with a single coat of protector, avoiding accumulation of excess product. Maintain a wet edge in order to prevent overlap marks.

Traffic: Pedestrian: 24 h. / Vehicular: 48 to 72 h. Block access during that period.

CAUTION

- Any new concrete product has the potential to produce efflorescence (whitish salts) on its surface. This Protector, like any film-forming coating, carries a small risk of trapping efflorescence beneath its film. Consult the paver manufacturer or contact Techniseal® at 1 800 465-7325 for more information.
- Do not attempt sprayer application on windy days.
- Do not apply this product over a blotchy or hazed surface.
- This product will make the surface more slippery when wet. If slipping is a problem, consider Techniseal® CB Protector or SureFoot anti-slip grit (245-970).
- An over-accumulation of product could lead to surface whitening.
- Extreme climate or heavy traffic could limit product longevity.

COVERAGE

1 gal. covers up to 150 sq. ft. Coverage will depend on surface porosity and joint width.

CLEANING & DISPOSAL

Wash tools with lacquer thinner. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

STORAGE AND SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container and stored in a dry and well ventilated place with controlled temperature (40°F to 75°F). Keep sheltered from weather and direct sunlight. Properly stored, the product's shelf life is 3 years following production (see date on packaging).

PACKAGING

Product Code	Pro Size	Units per box	Units per pallet
60301534 (121-133)	1 gal	4	180
60301535 (121-136)	5 gal.	-	48

WARNING



PROTECTOR for CONCRETE PAVERS - WL4

DANGER

Highly flammable liquid and vapor.
 Causes serious eye irritation.
 Causes skin irritation.
 May damage the unborn child.
 Suspected of damaging fertility.
 Suspected of causing cancer.
 May be fatal if swallowed and enters airways.
 May cause respiratory irritation.

May cause drowsiness and dizziness.

May cause damage to organs through prolonged or repeated exposure.

Read label before use. KEEP OUT OF THE REACH OF CHILDREN. If medical advice is needed, have product container or label at hand.

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 24.5%

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only nonsparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.

Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Store locked up. Store in a well-ventilated place. Keep cool.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Avoid contact with skin and clothing. Wash thoroughly after handling.

Defatting to the skin. Prolonged or repeated contact may dry skin and cause irritation.

Coating Category: Waterproofing Concrete/ Masonry Sealers (VOC Concentration Limit: 400g/L)

EMERGENCY PHONE: CANUTEC (613) 996-6666 / SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT

Techniseal®, 300 Liberté, Candiac (Québec), Canada J5R 6X1

SHIPPING

Land and sea

NOT REGULATED

LIMITED WARRANTY

Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m²). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.