



## Specification – DoorProtect Plus



Classification	Combined point magnetic contact and vibration radio channel security detector
Type of detector	Wireless
Installation method	Indoors
Compatibility	Operates only with Hub, Hub Plus, Hub 2 and ReX
Sensing element	Reed switch, accelerometer
Alarm signal delivery time	0.15 s
Activation threshold	Small magnet - 1 cm, Big magnet - 2 cm
Power supply	Battery: CR123A battery Power supply voltage: 3 V Battery life - up to 5 years
Jeweller radio technology	Communication range with central unit - up to 1,200 m in an open space Two-way communication between devices Operating frequencies - 868.0-868.6 MHz Self-adjusting RF output power - up to 20 mW Block encryption based on AES algorithm Device polling period - 12-300 s
Temperature sensor	Available
Operating temperature range	+5°C to +40°C
Permissible humidity	Up to 75%
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	Diameter: 20 mm Height: 90 mm
Weight	29 g
Certification	Grade 2, CE
Warranty	Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.
Complete set	DoorProtect Plus opening detector SmartBracket mounting panel Two Magnets External contact CR123A battery (pre-installed) Installation set User's guide