

# AJAX

## Specification – GlassProtect



Classification	Surface sound radio channel security detector
Type of detector	Wireless
Installation method	Indoors
Compatibility	Operates with Hub, Hub Plus, Hub 2, ReX, ocBridge Plus, uartBridge
Sensing element	Electret microphone
Break detection distance	Up to 9 m
Alarm signal delivery time	0.15 s
Sensitivity	Adjustable, 3 levels
Detection angle	180°
Power supply	Battery: CR123A battery Power supply voltage: 3 V Battery life - up to 7 years
Jeweller radio technology	Communication range with central unit - up to 1,000 m in an open space Two-way communication between devices Operating frequencies - 868.0-868.6 MHz Self-adjusting RF output power - up to 20 mW Block encryption based on AES algorithm Device polling period - 12-300 s
Temperature sensor	Available
Operating temperature range	+5°C to +40°C
Permissible humidity	Up to 75%
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	Diameter: 20 mm Height: 90 mm
Weight	30 g
Certification	Grade 2, CE
Warranty	Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.
Complete set	GlassProtect glass break detector SmartBracket mounting panel Two Magnets External contact CR123A battery (pre-installed) Installation set User's guide