



Classification	Radio channel security sounder
Type of siren	Wireless
Installation method	Indoors
Compatibility	Operates only with Hub, Hub Plus, Hub 2 and ReX
Type of notification	Sound
Connector for external LED	Available
Sound volume level	Adjustable, 81-105 dB at a distance of 1 m
Alarm length	Adjustable, 3-180 s
Indication of armed/disarmed status	Yes
Alarm signal delivery time	0,15 s
Power supply	Battery: CR123A battery Power supply voltage: 3 V Battery life - up to 5 years
Jeweller radio technology	Communication range with central unit - up to 2,000 m in an open space Two-way communication between devices Operating frequencies - 868.0-868.6 MHz Self-adjusting RF output power - up to 20 mW Block encryption based on AES algorithm Device polling period - 12-300 s
Temperature sensor	Available
Operating temperature range	From -10°C to +40°C
Permissible humidity	Up to 75%
Protection class of body	IP50
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	75x76x27 mm
Weight	97 g
Certification	Grade 2, CE
Warranty	Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.
Complete set	HomeSiren SmartBracket mounting panel Connector for LED indicator 2 x CR123A batteries (pre-installed) Installation set User's guide