



Classification	The radio channel central unit with the support of visual alarm verification detectors
Maximum number of devices connected	100
Video surveillance support	Up to 25 cameras or DVRs
Maximum number of users	50
Maximum number of rooms	50
Maximum number of groups	9
MotionCam detectors support	+
Communication channels	Ethernet, Two x 2G SIM-cards GSM (850/900/1800/1900 MHz)
Alarm signal	Delivery time: 0.15 s Types of notifications: SMS message, call, push
Switching between the SIM-cards	4 minutes
Communication with Central Monitoring Station	Contact ID, SIA
The speed of alarm delivery to the CMS	Instant
Operating system	OS Malevich
Power supply	Mains supply: 110-240 Vac Battery backup: Li-Ion 2A/h Up to 16 hours of offline operation when Power is switched off
Jeweller radio protocol	Communication range with central unit - up to 2,000 m in an open space Two-way communication between devices Operating frequencies - 868.0-868.6 MHz Self-adjusting RF output power - up to 25 mW Block encryption based on AES algorithm Device polling period - 12-300 s
Wings radio technology	Transmission of visual confirmations Delivery verification of packages
Operating temperature range	-10°C to +40°C
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Video surveillance	Up to 10 cameras or DVRs
Remote set up	+
Dimensions	163x163x36 mm
Weight	362g
Certification	Grade 2, CE
Warranty	Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.
Connected ReX	5



Scenarios	32
Complete set	Ajax Hub 2 intelligent control panel SmartBracket mounting panel Power cable Ethernet cable Installation Kit User Guide
