

# AJAX

## Specification – LeaksProtect



Classification	Radio channel water leak detector
Type of detector	Wireless
Installation method	Indoors
Compatibility	Operates with Hub, Hub Plus, Hub 2, ReX, ocBridge Plus, uartBridge
Alarm signal delivery time	0.15 s
False alarm filter	+
Interconnected alarms	+
Power supply	Battery: Two AAA Batteries Power supply voltage: 3 V Battery life - up to 5 years
Jeweller radio technology	Communication range with central unit - up to 1,300 m in an open space Two-way communication between devices Operating frequencies - 868.0-868.6 MHz Self-adjusting RF output power - up to 20 mW Block encryption based on AES algorithm Device polling period - 12-300 s
Temperature sensor	Available
Operating temperature range	+0°C to +50°C
Permissible humidity	Up to 100%
Protection class	IP65
Anti-sabotage	Protection against fraud Jamming detection Anti-Sabotage
Remote setting and testing	+
Dimensions	56x56x14 mm
Weight	40 g
Certification	EN 14604
Warranty	Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.
Complete set	LeaksProtect detector SmartBracket mounting panel 2 x AAA batteries (pre-installed) Installation set User's guide