

AJAX

Specification – StreetSiren



Classification	Light and sound radio channel security sounder
Type of siren	Wireless
Installation method	Indoors/outdoors
Compatibility	Operates only with Hub, Hub Plus, Hub 2 and ReX
Type of notification	Sound/light
Sound volume level	Adjustable, 85-113 dB at a distance of 1 m
Alarm length	Adjustable — 3-180 s
Indication of armed/disarmed status	Yes
Alarm signal delivery time	0.15 s
Power supply	Battery: 4 x CR123A batteries Power supply voltage: 3 V Battery life - up to 5 years Mains supply: DC 12 V±20%
Jeweller radio technology	Communication range with central unit - up to 1,500 m in an open space Two-way communication between devices Operating frequencies - 868.0-868.6 MHz Self-adjusting RF output power - up to 25 mW Block encryption based on AES algorithm Device polling period - 12-300 s
Temperature sensor	Available
Operating temperature range	From -25°C to +50°C
Permissible humidity	Up to 95%
Protection class of body	IP54
Anti-sabotage	Protection against fraud Jamming detection Tamper-resistant
Remote setting and testing	+
Dimensions	200x200x51 mm
Weight	528 g
Certification	Grade 2, CE
Warranty	Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.
Complete set	StreeSiren SmartBracket mounting panel 4 x CR123A batteries (pre-installed) Installation set User's guide