



Classification	Radio channel relay unit
Device type	Wireless
Installation method	Electrical back box
Compatibility	Operates only with Hub, Hub Plus, Hub 2 and ReX
Alarm signal delivery time	0.3 seconds
Actuating element	Relay
Voltage protection (supply)	For 230 V mains: max — 264 V, min — 161 V For 110 V mains: max — 126 V, min — 77 V
Maximum load current	13 A
Maximum current protection	Yes (13 A)
Maximum temperature protection	> 65°C
Permissible power	Resistive load at 230 V — up to 3 kW Resistive load at 110 V — up to 1.5 kW
Electric power meter function	Available
Energy consumption parameter check	Voltage
Alarm signal delivery time	0.15 s
Power supply	110-230 V±10% 50/60 Hz
Jeweller radio protocol	Communication range with central unit - up to 1,000 m in an open space Two-way communication between devices Operating frequencies - 868.0-868.6 MHz Self-adjusting RF output power - up to 25 mW Block encryption based on AES algorithm Device polling period - 12-300 s
Operating temperature range	0°C to +64°C
Permissible humidity	Up to 75%
Protection class of body	IP20
Anti-sabotage	Protection against fraud Jamming detection
Remote set up	+
Dimensions	39 × 33 × 18 mm
Weight	30 g
Certification	CE
Warranty	Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.
Complete set	Wall Switch Installation Set User Guide