



XTP120 12KW THREE-PHASE GENERATORS

		
	XTP120EH-208 XTP120EV-208	XTP120EH-480 XTP120EV-480
AC voltage	120/208 Vac	277/480 Vac
Rated output	12,000 W	12,000 W
Rated current	36 A	18 A
Starting system	Electric	Electric
Engine	Honda or Vanguard	Honda or Vanguard
Output power, approx.	21 hp	21 hp
Fuel capacity	7.25 gal. (27.4L)	7.25 gal. (27.4L)
Continuous run time	6.2 hrs. @ 50% load	6.2 hrs. @ 50% load
Fuel type	Unleaded	Unleaded
Receptacles	One 120V 20A duplex One 250V 50A straight-blade	One 480V 20A locking
Dimensions, L x W x H	44¾ x 25¾ x 28¾ in. (114 x 64 x 73cm)	44¾ x 25¾ x 28¾ in. (114 x 64 x 73cm)
Dry weight, approx.	330 lbs. (150kg)	330 lbs. (150kg)
Optional accessories	2-wheel kit 4-wheel kit	2-wheel kit 4-wheel kit
Deratings: Ratings apply for altitudes from sea level up to 1,000 feet (304.8 meters) with typical cooling, normal ambients and gasoline fuel. Reduce ratings 3.5% for each 1000 feet (305 meters) above sea level and 1.0% for each 10 °F rise above 60 °F (5.556 °C above 20 °C).		